Distributed by:

JAMECO® ELECTRONICS

**www.Jameco.com ✦ 1-800-831-4242**

The content and copyrights of the attached material are the property of its owner.

# MEAN WELL

## SWITCHING POWER SUPPLY

**ISO-9001 CERTIFIED MANUFACTURER**

**P25A-D DUAL SERIES**

**Jameco Part Number 221778 (P25A16-R1BU)**

.FULL RANGE AC INPUT
.IEC320-C14(3PIN INLET)
.FULLY ENCLOSED PLASTIC CASE
.100% FULL LOAD BURN-IN TEST
.LED INDICATE FOR POWER ON
.SHORT CIRCUIT PROTECTED
.OVER LOAD PROTECTION
.OVER TEMP. PROTECTED
.OVER VOLTAGE PROTECTED
.APPROVALS:UL/CUL/TUV/CB/CE
.MTBF:200000HRS BY MIL-HDBK-217F, NOTICE 2, PARTS COUNT

| ORDER NO. / SPECIFICATION | P25A13-yyy | | P25A14-yyy | | P25A16-yyy | |
|---|---|---|---|---|---|---|
| SAFETY MODEL NO. | PSU25A-13 | | PSU25A-14 | | PSU25A-16 | |
| DC OUTPUT VOLTAGE | +5V | +12V | +5V | +15V | +5V | +24V |
| OUTPUT V. TOLERANCE | ±5% | ±5% | ±5% | ±5% | ±5% | ±5% |
| OUTPUT RATED CURRENT | 2.5A | 1.0A | 2.5A | 0.8A | 2.5A | 0.5A |
| OUTPUT CURRENT RANGE | 0.5-2.5A | 0.1-1.0A | 0.5-2.5A | 0.1-0.8A | 0.5-2.5A | 0.1-0.5A |
| RIPPLE & NOISE | 50mVp-p | 100mVp-p | 50mV | 100mV | 50mV | 100mV |
| LINE REGULATION | ±1% | ±1% | ±1% | ±1% | ±1% | ±1% |
| LOAD REGULATION | ±5% | ±5% | ±5% | ±5% | ±5% | ±5% |
| DC OUTPUT POWER | 25W | | 25W | | 25W | |
| EFFICIENCY | 70% | | 72% | | 74% | |
| DC VOLTAGE ADJ. | FIXED | | | | | |
| INPUT VOLTAGE RANGE | 90~264VAC 47~63Hz | | | | | |
| AC CURRENT | 0.8A/100VAC | | | | | |
| AC INPUT CONNECTOR | IEC320-C14, 3PIN INLET | | | | | |
| INRUSH CURRENT | COLD START < 60A PEAK @ 230VAC | | | | | |
| LEAKAGE CURRENT | <0.75mA/240VAC | | | | | |
| OVERLOAD PROTECTION | HICCUP MODE, RESET:AUTO RECOVERY | | | | | |
| OVER VOLTAGE PROTECTION | 110%~140% | | | | | |
| TEMP. COEFFICIENT | ±0.03% / °C (0~50°C) | | | | | |
| SETUP, RISE, HOLD UP TIME | 200ms, 50ms, 16ms | | | | | |
| VIBRATION | 10~500Hz, 2G 10min./1cycle, PERIOD FOR 60min. EACH AXES | | | | | |
| WITHSTAND VOLTAGE | I/P-O/P:3KVAC, I/P-FG:1.5KVAC FOR 1min. | | | | | |
| ISOLATION RESISTANCE | I/P-O/P, I/P-FG: 100M Ohms min@500VDC | | | | | |
| WORKING TEMP., HUMIDITY | 0°C~+30°C @ 100%LOAD, 40°C @ 70% LOAD, 20%~90% RH | | | | | |
| STORAGE TEMP., HUMIDITY | -20°C~+85°C, 10%~95% RH | | | | | |
| DIMENSION | 108*67*36mm (L*W*H) | | | | | |
| WEIGHT; Q'TY/CARTON | 0.3Kgs; 54PCS/CARTON | | | | | |
| SAFETY STANDARDS | UL1950, CSA22.2, EN60950 APPROVAL | | | | | |
| EMC STANDARDS | EN55022 CLASS B, EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11,EN55024 VERIFICATION | | | | | |
| LENGTH OF OUTPUT CABLE | 150cm OF AWM 2464X4C,WITH SHIELDING(TYPICAL) | | | | | |
| PLUG OF DC OUTPUT | STANDARD PLUG R1B:DIN 5 PIN<br>yyy:TO BE DEFINED BY OUTPUT CABLE AND CONNECTOR | | | | | |

NOTE:
1.ALL PARAMETERS ARE SPECIFIED AT 230VAC INPUT, RATED LOAD, 25°C 70% RH. AMBIENT.
2.TOLERANCE: INCLUDE SET UP TOLERANCE, LINE REGULATION, LOAD REGULATION.
3.RIPPLE & NOISE ARE MEASURED AT 20MHz BY USING A 12" TWISTED PAIR TERMINATED WITH A 0.1uF & 47uF CAPACITOR.
4.LINE REGULATION IS MEASURED FROM LOW LINE TO HIGH LINE AT RATED LOAD.
5.LOAD REGULATION IS MEASURED FROM 20% TO 100% RATED LOAD.

2003-01-24